



A sharp competitive edge
with a *powerful* pro flatbed



Pro power

It's what gives the EFI™ Pro 24f LED flatbed printer its sharp competitive edge. It contains the most powerful features — from LED and variable-drop greyscale head technology to its true flatbed design with moving gantry and multi-zoned vacuum table. It's the strategic choice for printers producing graphic arts, art reproductions, membrane switches, graphic overlays — and other speciality applications up to 5 cm thick — as well as overflow printing and where precision and fine detail, image quality, and speed are critical to meeting customers' demands.

The EFI Pro 24f flatbed printer delivers the most powerful results with outstanding image quality at production speeds, broad colour gamut, optimised ink usage, and access to more profitable jobs.

At a glance

- True flatbed architecture with moving carriage and gantry over a 1.2 m x 2.4 m bed and a vacuum system to hold media stationary on a flat surface, ensuring accurate registration for multiple over-prints or panels
- Four colours plus dual channels of white standard, and single-pass, multilayer printing
- Variable-drop greyscale print capability for high-quality imaging
- LED for lower power consumption, less waste, and the use of thinner substrates
- Four user-selectable vacuum zones designed to match the most common media sizes without masking, ensuring efficient hold-down, no unintended media movement, and easy transitions between jobs
- Easy edge-to-edge printing (full bleed), reducing finishing time
- Multi board, including different size boards, printing simultaneously
- Includes an EFI Fiery® proServer Core digital front end featuring FAST RIP acceleration technology, plus RIP and print on demand functionality or the ability to print pre-ripped files at the printer interface
- Ideal for printing high-value applications, such as lenticulars and photographic backlit displays, exotic materials, and irregularly shaped or heavy objects

FAST RIP



The power of green LED technology



From the leaders in production-level LED inkjet printing, EFI's brilliantly designed "cool cure" LED curing technology empowers you to do more for less. Increase your profit opportunity by offering more premium-margin jobs while reducing operating costs and your environmental footprint:

- Extends your range of supported substrates, including lower-cost and added-value speciality media
- Increases uptime and productivity with instant on/off and less maintenance
- Drives down operating costs with less energy consumption and fewer consumable parts
- Reduces waste with consistent colour output and simple operation
- Satisfies customer requests for a greener print solution with low VOCs, lower power consumption, and less waste and consumables



EFI Pro 24f

Features and benefits

- Standard: CMYK plus two White channels
- Dynamic curing LED UV lamps
- Up to 107 m²/hr
- Up to 1200 x 1200 dpi
- Up to four levels of variable-drop greyscale
- Integration ready with EFI web-to-print and MIS/ERP solutions with native JDF connectivity
- Ships with an EFI Fiery proServer Core digital front end
- RIP and print on demand, or print pre-ripped files at the printer interface
- One-year Enhanced Service Program (ESP) warranty covers your printer, Fiery proServer Core, and Fiery XF software
- Twelve months of Essential level coverage – three-business-day response

Media/handling

- Four-zone, user-selectable vacuum system
- Table width: 291.8 cm
- Maximum printable area: 254 cm x 132 cm
- Maximum media thickness: 5.08 cm
- Maximum media weight: 180 kg evenly distributed

Productivity

- White printing at one-half CMYK speeds

MODE	M ² /HR	1.2 M X 2.4 M BOARDS/HR
Ultra quality	7	2
High quality	13	4
POP quality	20	6
Production mode	27	9
Distant view/ outdoor mode	57	19
Express mode	107	36

Formats

All popular desktop files formats, including PostScript® 3™, EPS, TIFF, PDF, and RGB/CMYK

Environmental considerations

- Temperature: 20-30 °C
- Humidity: 30%-80% (non-condensing)
- Ventilation required but not supplied with the system
- Weight: 1,599.82 kg uncrated
- Dimensions (W x D x H): 446.5 cm x 208 cm x 138.9 cm
- Electrical: 208-240 VAC, single phase, 50/60 Hz, 20 amp average running (50 amp peak)

EFI fuels success.

We develop breakthrough technologies for the manufacturing of signage, packaging, textiles, ceramic tiles, and personalised documents, with a wide range of printers, inks, digital front ends, and a comprehensive business and production workflow suite that transforms and streamlines the entire production process, increasing your competitiveness and boosting productivity. Visit www.efi.com or call 0808 101 3484 (UK only) or +44 (0)1246 298000 for more information.

