vivid.

easymount® AIR

EM-A1600SH WIDE FORMAT LAMINATING SYSTEM

KEY FEATURES

- Pneumatic air pressure
- 10m/33ft a minute
- 30mm/1 3/16" mounting thickness
- Variable speed control
- Foot pedal
- Reverse mode
- Multilingual control panel

GREAT FOR USE IN

- Sign makers
- Print finishers

IDEAL WHEN LAMINATING

- Posters, graphics and signs
- Mounting prints to board
- Pop-up displays
- Applying vinyls, tapes and adhesive films
- Outdoor signage

and many more...

Easymount Air® is a revolutionary product in the wide format lamination & mounting market.

2016 Top Products Wide-Format&Signage

Design & Performance

The patented technology within the Easymount Air uses one of the most advanced concepts ever seen in a wide format laminator. Pneumatic air pressure controls the laminating rollers, allowing you to mount and laminate with incredible accuracy and speed.

This new technology allows the roller to adjust to the exact thickness and pressure required, giving faster production times. The pneumatic air allows the roller to float down; ensuring Foamex and fluted boards are not crushed. When the rollers achieve the correct board thickness, the roller can be locked in place to keep the required gap, making board feeding more accurate. Mechanical wedges, often used to lock the roller by other pneumatic systems, are not required.

Specifications

	EM-A1600SH
Laminating Speed (m/ft/min)	10m/33ft
Max. Width (mm/inches)	1600mm/63"
Mounting Thickness (mm/inches)	30mm/1 3/16"
Roller Diameter (mm/inches)	130mm/5"
Laminating Temperature (°C/°F)	0-60°C/32-140°F
Control Panel	Digital
Pressure Adjustment	Pneumatic
Film Core (mm/inches)	77mm/3"
Power Supply AC (V–Hz)	220/240–50-60
Power Consumption (W)	1500
Overall Dimensions (mm/inches)	2190x650x1255mm/86x26x49"
Gross Machine Weight (Kg/lbs)	245Kg/540lbs
Warranty	1 year

Features

- Solid heavy duty construction
- Release liner take-up
- Adjustable rollers up to 30mm/1 3/16"
- Large rollers for even pressure
- Handy reverse mechanism
- Foot pedal for controlled operation



Patented pneumatic rollers 'float' down and will not crush soft materials like Correx®.

Speed Control

Reverse Mode

CMYUK
SPECIALISTS IN SUPERWIDE DIGITAL PRINT

T. +44 (0) 1743 810000 W. www.cmyuk.com

DEMO & TRAINING CENTRE:
UNIT 3B, VANGUARD WAY, BATTLEFIELD ENTERPRISE PARK, SHREWSBURY, SY1 3TG

HEAD OFFICE:
UNIT 15, HEADLEY PARK TEN, HEADLEY ROAD EAST, WOODLEY, BERKSHIRE, RG5 4SW

T. +44 (0) 118 989 2929