

Product Bulletin

GF-201OPAE

FLEXIBLE WHITE MATTE PVC

Permanent Adhesive

GF-201OPAE (Air Egress) is a 85 mic premium matte white flexible polymeric vinyl film coated with permanent gray solvent-acrylic pressure sensitive adhesive laminated to a 135 gsm AE layflat liner. This film is designed to accept a variety of solvent-based, UV curable and latex inks common to wide format digital printing systems. Adhesive offers good opacity with low initial tack building to a permanent bond within 24 hours providing repositionability to the graphic during application. The 135 gsm AE liner offers excellent product layflat in a variety of ambient conditions along with ease of application for large format graphics.

Applications	GF-201OPAE is designed for large format interior or exterior signage, decals, nameplates and point-of-purchase displays.	
Thickness	Film	85 mic.
	Adhesive	25 mic
	Liner	135 gsm.
	(Thickness variance +/- 10%)	
Dimensional Stability	Good.	
Temperature Ranges	Minimum application temperature	+4,4°Celsius
	Service temperature	-40°C bis +82°C.
Expected Exposure Exterior	Up to 7 years unprinted under normal exposure conditions.	
Adhesion Average bond	To stainless steel	12N/25mm
	PSTC-101 Method A with 24 hr. dwell at 21°C and 50% relative humidity. Typical values. Individual values may vary. Test your application thoroughly.	
Water Resistance	Good. Test if immersed.	
Humidity Resistance	Good.	
Lösungsmittelbeständigkeit	Good.	
Solvent Resistance	12-month shelf life when stored at 21°C and 50% relative humidity	
Product Series	GF-201OPAE 1,37m x 50m	



*Manufacturer of Pressure Sensitive Films, Traffic Graffix
Floor Advertising Films, Custom Coatings and Printing
Inks.*

309 S. Union • P.O. Box 158 • Sparta, Michigan 49345 • (616) 887-7387 • (800)253-3664 • FAX (616)887-0537

Web Site: www.generalformulations.com • e-mail: gfiinfo@generalformulations.com

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to General Formulations, Inc's Price List for Terms and Conditions or Sale, Including Disclaimer of Warranties and Limitation of Liability.